

834S LIV 15069



834S LIV 15069
PRINTEMPS 130

drapilux
By Sotexpro

DRAPILUX GmbH - Hafenstraße 3, 77694 Kehl - Deutschland

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected



834S LIV 15069 AUTOMNE 205

Light and aerial gauze, the 834 S offers privacy meanwhile letting the light get through, its weaving technique gives it a great finesse and a good resistance.

Technical properties



Flame retardant



Sheer

Applications Roman blinds - Panel curtains - Curtains

Composition polyester/polyester FR

Weight 40 g/m² Width 280 cm

Fabric direction Room High Direction Fitting ↔ 100.0 cm ↓ 300.0 cm

Maintenance advice     

Labels France Terre Textile (R016)

Minimum order 1 linear(s) meter(s)

Technical characteristics

Flame retardant	M1 / B1 / IMO PASS	
Transparent veil	Yes	
Resilience	Lightfastness (units Class/8)	6
	Dimensional Stability (%)	
	Warp	0.5
	Weft	0
	Breaking Elongation	
	Warp	36
	Weft	33
	Breaking load (daN)	
Warp	31	
Weft	23	

drapilux
By Sotexpro

DRAPILUX GmbH - Hafenstraße 3, 77694 Kehl - Deutschland

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected