



ASTRAL



ASTRAL abricot 08




ASTRAL aubergine 27



ASTRAL perle 96




ASTRAL sienne 29



ASTRAL anthracite 38




ASTRAL océan 91




ASTRAL arctique 58




ASTRAL blanc 01



ASTRAL mastic 48



ASTRAL crème 02




ASTRAL taupe 95



ASTRAL noir 10




ASTRAL BPI 00



ASTRAL Beige 63




ASTRAL Safran 49



ASTRAL Terre 107




ASTRAL Chamois 111



ASTRAL Bordeaux 04



ASTRAL Ecume 82




ASTRAL Sapin 126

drapilux
By Sotexpro


DRAPILUX GmbH - Hafenstraße 3, 77694 Kehl - Deutschland

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected

ASTRAL



ASTRAL Kaki 148



ASTRAL Amande 75

This plain fabric blocks out light very effectively and is available in a wide variety of colours.

Technical properties








Thermal

Applications Roman blinds - Panel curtains - Curtains

Composition 100% polyester with white flocked acrylic backing

Weight 280 g/m² Width 280 cm

Fabric direction Room high or standard direction Fitting ↔ cm ↓ cm

Maintenance advice     

Minimum order 25 linear(s) meter(s)

Technical characteristics

Flame retardant

EN13773 : 2003 Class 1 / BS 5867 TYPE C / B1 / IMO PASS / UNI 8456 / 9174 Classe Uno

Optical index

Light reflexion : **82 %**

Light absorption : **18 %**

Light transmission : **0 %**

Thermal index

Solar reflexion : **74 %**

Solar absorption : **26 %**

Solar transmission : **0 %**

UV transmission : **0 %**

Gtot : **Gt 33 % Fc 55 %**

Resilience

Lightfastness (units Class/8) **5**

Dimensional Stability (%)

Warp **-0.5**

Weft **0**

Breaking Elongation

Warp **26**

Weft **15**

Breaking load (daN)

Warp **62**

Weft **31**

drapilux
By Sotexpro

DRAPILUX GmbH - Hafenstraße 3, 77694 Kehl - Deutschland

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected