

# COLLIOURE



COLLIOURE Olive 61



COLLIOURE Agrume 69



COLLIOURE Miel 17



COLLIOURE Mandarine  
93



COLLIOURE Océan 91



COLLIOURE Pervenche  
13




COLLIOURE Ardoise 08




COLLIOURE Glacier 43




COLLIOURE Souris 31




COLLIOURE Ivoire 02




COLLIOURE Naturel 26



COLLIOURE Brun 23



COLLIOURE Titanium 98




COLLIOURE Noir 12



COLLIOURE eucalyptus  
117



COLLIOURE navy 120



COLLIOURE lin 11



COLLIOURE marine 25



COLLIOURE  
Bergamotte 121



COLLIOURE Absinthe  
132

**drapilux**  
By Sotexpro

DRAPILUX GmbH - Hafenstraße 3, 77694 Kehl - Deutschland

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected

# COLLIOURE



COLLIOURE Arctique 58



COLLIOURE Saumon  
143




COLLIOURE Tomette 60



COLLIOURE Terre 107



COLLIOURE Aubergine  
27




COLLIOURE Cacao 168



COLLIOURE Chataigne  
55



COLLIOURE Chamois  
111





COLLIOURE Pêche 52

**drapilux**  
By Sotexpro

DRAPILUX GmbH - Hafenstraße 3, 77694 Kehl - Deutschland

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected



# COLLIOURE Blanc 01

This plain twill fabric comes in a range of several colours.

## Technical properties



Flame retardant



Thermal

**Applications** Roman blinds - Panel curtains - Valences - Curtains - Cushions - Decorative frames

**Composition** 100% FR polyester

**Weight** 270 g/m<sup>2</sup> **Width** 140 cm / 280 cm

**Fabric direction** Room high or standard direction **Fitting** ↔ cm ↓ cm

**Maintenance advice**     

**Labels** France Terre Textile (R016)

**Certifications** OEKO-TEX STANDARD 100 (CQ 1006/1)

**Minimum order** 1 linear(s) meter(s)



## Technical characteristics

Flame retardant

M1 / EN13773 : 2003 Class 1 / B1 / IMO PASS / UNI 8456 / 9174 Classe Uno

Optical index

Light reflexion : **64 %**

Light absorption : **19 %**

Light transmission : **17 %**

Thermal index

Solar reflexion : **64 %**

Solar absorption : **17 %**

Solar transmission : **19 %**

UV transmission : **3 %**

Gtot : **Gt 36 % Fc 61 %**

Resilience

Lightfastness (units Class/8) **6**

Pilling **2-3**

Dimensional Stability (%)

Warp **-3**

Weft **-0.5**

Martindale (Cycles) **35000**

Breaking Elongation

Warp **26**

Weft **28**

Breaking load (daN)

Warp **100**

Weft **160**

**drapilux**  
By Sotexpro

DRAPILUX GmbH - Hafenstraße 3, 77694 Kehl - Deutschland

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected