




# COLLIOURE




COLLIOURE Olive 61




COLLIOURE Agrume 69




COLLIOURE Miel 17




COLLIOURE Mandarine  
93




COLLIOURE Océan 91




COLLIOURE Pervenche  
13




COLLIOURE Ardoise 08




COLLIOURE Glacier 43




COLLIOURE Souris 31




COLLIOURE Blanc 01




COLLIOURE Ivoire 02




COLLIOURE Naturel 26



COLLIOURE Brun 23




COLLIOURE Titanium 98




COLLIOURE Noir 12




COLLIOURE eucalyptus  
117



COLLIOURE navy 120



COLLIOURE lin 11



COLLIOURE marine 25




COLLIOURE  
Bergamotte 121

**drapilux**  
By Sotexpro

DRAPILUX GmbH - Hafenstraße 3, 77694 Kehl - Deutschland

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected


# COLLIOURE




COLLIOURE Absinthe  
132




COLLIOURE Arctique 58




COLLIOURE Saumon  
143




COLLIOURE Tomette 60




COLLIOURE Terre 107




COLLIOURE Aubergine  
27




COLLIOURE Cacao 168



COLLIOURE Chamois  
111



COLLIOURE Pêche 52



# COLLIOURE Chataigne 55

This plain twill fabric comes in a range of several colours.

## Technical properties



Flame retardant





Thermal

**Applications** Roman blinds - Panel curtains - Valences - Curtains - Cushions - Decorative frames

**Composition** 100% FR polyester

**Weight** 270 g/m<sup>2</sup> **Width** 140 cm / 280 cm

**Fabric direction** Room high or standard direction **Fitting** ↔ cm ↓ cm

**Maintenance advice**   

**Labels** France Terre Textile (R016)

**Certifications** OEKO-TEX STANDARD 100 (CQ 1006/1)

**Minimum order** 1 linear(s) meter(s)

## Technical characteristics

Flame retardant	M1 / EN13773 : 2003 Class 1 / B1 / IMO PASS / UNI 8456 / 9174 Classe Uno	
Optical index	Light reflexion :	64 %
	Light absorption :	19 %
	Light transmission :	17 %
Thermal index	Solar reflexion :	64 %
	Solar absorption :	17 %
	Solar transmission :	19 %
	UV transmission :	3 %
	Gtot :	<b>Gt 36 % Fc 61 %</b>
Resilience	Lightfastness (units Class/8)	6
	Dimensional Stability (%)	
	Warp	-3
	Weft	-0.5
	Breaking Elongation	
	Warp	26
	Weft	28
	Breaking load (daN)	
Warp	100	
Weft	160	

**drapilux**  
By Sotexpro

DRAPILUX GmbH - Hafenstraße 3, 77694 Kehl - Deutschland

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected