

NOCLIN MURA 2334



NOCLIN MURA 2334
Ivoire 115



NOCLIN MURA 2334
Savane 185



NOCLIN MURA 2334
Rose 129



NOCLIN MURA 2334
Grenat 56



NOCLIN MURA 2334
Terre 107



NOCLIN MURA 2334
Cassis 97



NOCLIN MURA 2334
Olive 61



NOCLIN MURA 2334
Turquoise 53



NOCLIN MURA 2334
Saphir 106



NOCLIN MURA 2334
Glacier 43



NOCLIN MURA 2334
Mastic 48



NOCLIN MURA 2334
Minéral 157



NOCLIN MURA 2334
Fusain 71



NOCLIN MURA 2334 Dune 170

False plain design printed on our Blackout double-side Noclin, the Mura design is inspired by the asperities and shades of a wall aged by time as to create a subtle material effect.

Technical properties






Thermal

Applications Roman blinds - Panel curtains - Curtains

Composition Polyester enduction acrylique

Weight 380 g/m² 1064 g/m² Width 280 cm

Fabric direction Room High Direction Fitting ↔ cm ↓ cm

Maintenance advice   

Minimum order 1 linear(s) meter(s)

Technical characteristics

Flame retardant	B1 / IMO PASS	
Optical index	Light reflexion :	53 %
	Light absorption :	47 %
	Light transmission :	0 %
Thermal index	Solar reflexion :	64 %
	Solar absorption :	36 %
	Solar transmission :	0 %
	UV transmission :	0 %
	Gtot :	Gt 36 % Fc 61 %
Resilience	Lightfastness (units Class/8)	4
	Dimensional Stability (%)	
	Warp	-1
	Weft	-1
	Breaking Elongation	
	Warp	48
	Weft	72
	Breaking load (daN)	
Warp	51	
Weft	84	

drapilux
By Sotexpro

DRAPILUX GmbH - Hofenstraße 3, 77694 Kehl - Deutschland

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected