




NOCTURNE



NOCTURNE Océan 91




NOCTURNE Arctique 58




NOCTURNE Cyan 90



NOCTURNE Mousse 92



NOCTURNE Abricot 08



NOCTURNE Orange 15




NOCTURNE Fuchsia 33




NOCTURNE Sienne 29



NOCTURNE Perle 96




NOCTURNE Grisé 03




NOCTURNE Crème 02




NOCTURNE Mastic 48




NOCTURNE Brun 23



NOCTURNE Taupe 95




NOCTURNE Noir 10




NOCTURNE anthracite
38



NOCTURNE absinthe
132



NOCTURNE aubergine
27



NOCTURNE Chamois
111



NOCTURNE Bordeaux
04

drapilux
By Sotexpro

DRAPILUX GmbH - Hafenstraße 3, 77694 Kehl - Deutschland

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected

NOCTURNE




NOCTURNE Rubis 59



NOCTURNE Saumon
143



NOCTURNE Or 94




NOCTURNE Terre 107




NOCTURNE Amande 75



NOCTURNE
Bergamotte 121




NOCTURNE Tilleul 103




NOCTURNE Prairie 125




NOCTURNE Sapin 126




NOCTURNE Ecume 82




NOCTURNE Beige 63



NOCTURNE Galet 147



NOCTURNE BPI 00



NOCTURNE Mordoré 133

This blackout fabric is very efficient. It is available in a wide range of colors

Technical properties



Flame retardant




Thermal

Applications Roman blinds - Panel curtains - Lining - Curtains

Composition 100% polyester with white flocked acrylic backing

Weight 280 g/m² **Width** 280 cm

Fabric direction Room high or standard direction **Fitting** ↔ cm ↓ cm

Maintenance advice     

Minimum order 1 linear(s) meter(s)

Technical characteristics

Flame retardant	M1 / BS 5867 TYPE C / B1 / IMO PASS		
Optical index	Light reflexion :	71 %	
	Light absorption :	29 %	
	Light transmission :	0 %	
Thermal index	Solar reflexion :	66 %	
	Solar absorption :	34 %	
	Solar transmission :	0 %	
	UV transmission :	0 %	
	Gtot :	Gt 35 % Fc 60 %	
Resilience	Lightfastness (units Class/8)	5	
	Pilling	3-4	
	Dimentional Stability (%)	Warp	-0.5
		Weft	0
	Martindale (Cycles)	40000	
	Breaking Elongation	Warp	19
		Weft	22
	Breaking load (daN)	Warp	37
		Weft	57

drapilux
By Sotexpro

DRAPILUX GmbH - Hofenstraße 3, 77694 Kehl - Deutschland

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on supports selected