



OPALE 2




OPALE 2 Océan 91




OPALE 2 Tomette 60




OPALE 2 Anthracite 38




OPALE 2 Souris 40




OPALE 2 Nacre 04




OPALE 2 Crème 02




OPALE 2 Sable 67



OPALE 2 Beige 63




OPALE 2 Brun 23




OPALE 2 Mastic 48




OPALE 2 Marine 25



OPALE 2 Paille 06




OPALE 2 Titanium 98




OPALE 2 Noir 36




OPALE 2 emeraude 88



OPALE 2 taupe 95



OPALE 2 absinthe 132



OPALE 2 lin 11



OPALE 2 Poterie 167



OPALE 2 Moutarde 21

drapilux
By Sotexpro


DRAPILUX GmbH - Hofenstraße 3, 77694 Kehl - Deutschland

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected

OPALE 2




OPALE 2 Olive 61



OPALE 2 Billard 86



OPALE 2 Peau 201





OPALE 2 Pêche 52



OPALE 2 Etang 165



OPALE 2 Glacier 43



OPALE 2 Moka 12

This plain fabric blocks out light very effectively and is available in a wide variety of colours.

Technical properties



Flame retardant

Applications Roman blinds - Roller blinds - Panel curtains - Curtains

Composition 100% polyester with white flocked acrylic backing

Weight 290 g/m² 406 g/m² Width 140 cm

Fabric direction Standard Direction Fitting ↔ cm ↓ cm

Maintenance advice

Minimum order 1 linear(s) meter(s)



Technical characteristics

Flame retardant	M1 / IMO PASS	
Optical index	Light reflexion :	72 %
	Light absorption :	28 %
	Light transmission :	0 %
Thermal index	Solar reflexion :	65 %
	Solar absorption :	35 %
	Solar transmission :	0 %
	UV transmission :	0 %
	Gtot :	Gt 35 % Fc 60 %
Resilience	Lightfastness (units Class/8)	5
	Breaking Elongation	
	Warp	35
	Weft	11



DRAPILUX GmbH - Hafenstraße 3, 77694 Kehl - Deutschland

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected