



# SOFTLINE



SOFTLINE Blanc 01




SOFTLINE Champagne  
02




SOFTLINE Perle 96




SOFTLINE Vieux rose 64



SOFTLINE Menthe 122



SOFTLINE Océan 91





SOFTLINE Anthracite 38

**drapilux**  
By Sotexpro

DRAPILUX GmbH - Hafenstraße 3, 77694 Kehl - Deutschland

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected



# SOFTLINE Parchemin 145

Light and soft canvas with peach skin touch, ideal for slightly filtering light into a room. The Softline can also be used as a lining to provide an extra finishing to your double-lined curtains.

## Technical properties



Flame retardant





Thermal

Applications Roman blinds - Panel curtains - Lining - Curtains

Composition 100% FR polyester

Weight 80 g/m<sup>2</sup> Width 290 cm

Fabric direction Room high or standard direction Fitting ↔ cm ↓ cm

Maintenance advice     

Minimum order 1 linear(s) meter(s)

## Technical characteristics

Flame retardant	M1 / B1 / IMO PASS	
Optical index	Light reflexion :	41 %
	Light absorption :	43 %
	Light transmission :	16 %
Thermal index	Solar reflexion :	52 %
	Solar absorption :	23 %
	Solar transmission :	25 %
	UV transmission :	1 %
	Gtot :	Gt 40 % Fc 68 %
Resilience	Lightfastness (units Class/8)	3
	Dimensional Stability (%)	
	Warp	-0.5
	Weft	-0.5
	Breaking Elongation	
	Warp	25
	Weft	10
	Breaking load (daN)	
	Warp	45
Weft	23	

**drapilux**  
By Sotexpro

DRAPILUX GmbH - Hafenstraße 3, 77694 Kehl - Deutschland

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected