

VEGA ELAINA 2165




VEGA ELAINA 2165
Coco 142



VEGA ELAINA 2165
Galet 147




VEGA ELAINA 2165
Peau 201



VEGA ELAINA 2165
Souris 31



VEGA ELAINA 2165
Tourterelle 138




VEGA ELAINA 2165
Cendre 145



VEGA ELAINA 2165
Caramel 174




VEGA ELAINA 2165
Poterie 167



VEGA ELAINA 2165
Banane 160



VEGA ELAINA 2165 Kaki
148



VEGA ELAINA 2165
Prusse 158




VEGA ELAINA 2165
Indigo 144



VEGA ELAINA 2165
Dune 170



VEGA ELAINA 2165
Moka 12



VEGA ELAINA 2165
Givre 161



VEGA ELAINA 2165
Cannelle 152



VEGA ELAINA 2165
Mordoré 133



VEGA ELAINA 2165
Sauge 182





VEGA ELAINA 2165
Sapin 126

drapilux
By Sotexpro

DRAPILUX GmbH - Hofenstraße 3, 77694 Kehl - Deutschland

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected



VEGA ELAINA 2165 Prune 84

Technical properties

Applications Roman blinds - Panel curtains - Curtains

Composition 100% polyester with white flocked acrylic backing

Weight 390 g/m² 1014 g/m² Width 260 cm

Fabric direction Standard Direction Fitting ↔ cm ↓ cm

Maintenance advice ☒ ☒ ☒ ©

Minimum order 25 linear(s) meter(s)

Technical characteristics

Flame retardant	EN13773 : 2003 Class 1 / BS 5867 TYPE B / B1 / IMO PASS	
Resilience	Lightfastness (units Class/8)	4
	Dimensional Stability (%)	
	Warp	-1
	Weft	0
	Breaking Elongation	
	Warp	69
	Weft	106
	Breaking load (daN)	
	Warp	52
Weft	41	

drapilux
By Sotexpro

DRAPILUX GmbH - Hafenstraße 3, 77694 Kehl - Deutschland

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected