



ASTRAL Bordeaux 04

This plain fabric blocks out light very effectively and is available in a wide variety of colours.

Technical properties



Thermal

Applications Roman blinds - Panel curtains - Curtains

Composition 100% polyester with white flocked acrylic backing

Weight 280 g/m² Width 280 cm

Fabric direction Room high or standard direction Fitting ↔ cm ↓ cm

Maintenance advice     

Minimum order 25 linear(s) meter(s)

Technical characteristics

Flame retardant

EN13773 : 2003 Class 1 / BS 5867 TYPE C / B1 / IMO PASS / UNI 8456 / 9174 Classe Uno

Optical index

| | |
|----------------------|------|
| Light reflexion : | 82 % |
| Light absorption : | 18 % |
| Light transmission : | 0 % |

Thermal index

| | |
|----------------------|-----------------|
| Solar reflexion : | 74 % |
| Solar absorption : | 26 % |
| Solar transmission : | 0 % |
| UV transmission : | 0 % |
| Gtot : | Gt 33 % Fc 55 % |

Resilience

| | |
|-------------------------------|------|
| Lightfastness (units Class/8) | 5 |
| Dimensional Stability (%) | |
| Warp | -0.5 |
| Weft | 0 |
| Breaking Elongation | |
| Warp | 26 |
| Weft | 15 |
| Breaking load (daN) | |
| Warp | 62 |
| Weft | 31 |

drapilux
By Sotexpro

DRAPILUX GmbH - Hafenstraße 3, 77694 Kehl - Deutschland

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected