ASTRAL BPI 00
Printing support



SCOURTIN Bergamote 121
Print pattern

Visual not taking into account the printing medium, the final rendering may vary according to the chosen medium.

Printing support **ASTRAL BPI 00**
Print pattern **SCOURTIN Bergamote 121**

Blackout Print Support

Technical properties

Flame retardant

Thermal

Applications Roman blinds - Panel curtains - Curtains

Composition 100% polyester with white flocked acrylic backing

Weight 280 g/m²

Width 280 cm

Fabric direction Room high or standard direction

Fitting ↔ cm ↕ cm

Maintenance advice

Label

Minimum order 25 linear(s) metter(s)

Technical characteristics

Flame retardant	EN13773 : 2003 Class 1 / BS 5867 TYPE C / B1 / IMO PASS / UNI 8456 / 9174 Classe Uno	
Optical index	Light reflexion :	**82 %**
	Light absorption :	**18 %**
	Light transmission :	**0 %**
Thermal index	Solar reflexion :	**74 %**
	Solar absorption :	**26 %**
	Solar transmission :	**0 %**
	UV transmission :	**0 %**
	Gtot :	**Gt 33 % Fc 55 %**
Resilience	Lightfastness (units Class/8)	**5**
	Dimentional Stability (%)	
	Warp	**-0,5**
	Weft	**0**
	Breaking Elongation	
	Warp	**26**
	Weft	**15**
	Breaking load (daN)	
	Warp	**62**
	Weft	**31**

Print pattern SCOURTIN


SCOURTIN Beige 63

SCOURTIN Fuchsia 33


SCOURTIN Sapin 126

SCOURTIN Anthracite 38


SCOURTIN Violine 105


SCOURTIN Pacifique 54


SCOURTIN Rose 129

SCOURTIN Blanc 01


SCOURTIN Lin 11


SCOURTIN Naturel 26


SCOURTIN Citrouille 136


SCOURTIN Turquoise 53


SCOURTIN Brun 23


SCOURTIN Hortensia 134


SCOURTIN Orage 123


SCOURTIN Rubis 59


SCOURTIN Ficelle 09


SCOURTIN Maïs 37


SCOURTIN Céladon 135


SCOURTIN Ebene 113

DRAPILUX GmbH - Hafenstraße 3, 77694 Kehl - Deutschland

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected

Print pattern SCOURTIN

SCOURTIN Tourterelle 138


SCOURTIN Titanium 98


SCOURTIN Lagon 110


SCOURTIN Gris 97

DRAPILUX GmbH - Hafenstraße 3, 77694 Kehl - Deutschland

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected