



BELORA Beige 90

This plain dimout fabric comes in a range of several colours. It does not have an M1 fire rating.

Technical properties



Thermal



Acoustic

Applications Roman blinds - Lining - Curtains

Composition 100% polyester

Weight 260 g/m² Width 290 cm

Fabric direction Room high or standard direction Fitting ↔ cm ↓ cm

Maintenance advice

Certifications OEKO-TEX STANDARD 100 (CQ 1006/1)

Minimum order 30 linear(s) meter(s)

Technical characteristics

| | | |
|-----------------|---|------------------------|
| Flame retardant | NF 12952 | |
| Acoustic | Noise reduction coefficient (NRC) : | 0.88 |
| | Weighted sound absorption coefficient (a _w) : | 0.90 |
| | Acoustic absorption class (a _w) : | A |
| Optical index | Light reflexion : | 55 % |
| | Light absorption : | 45 % |
| | Light transmission : | 0 % |
| Thermal index | Solar reflexion : | 53 % |
| | Solar absorption : | 47 % |
| | Solar transmission : | 0 % |
| | UV transmission : | 0 % |
| | Gtot : | Gt 40 % Fc 67 % |
| Resilience | Lightfastness (units Class/8) | 6 |
| | Dimentional Stability (%) | |
| | Warp | 0 |
| | Weft | 0 |
| | Breaking Elongation | |
| | Warp | 17 |
| | Weft | 27 |
| | Breaking load (daN) | |
| | Warp | 87 |
| | Weft | 110 |

drapilux
By Sotexpro

DRAPILUX GmbH - Hafenstraße 3, 77694 Kehl - Deutschland

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected