




BELORA BPI 00
Printing support



SALIN Vert 24
Print pattern



Printing support **BELORA BPI 00** Print pattern **SALIN Vert 24**

Dimout support for digital printing. It does not have an M1 fire rating.

Technical properties



Flame retardant



Thermal



Acoustic

Applications Roman blinds - Panel curtains - Lining - Curtains

Composition 100% polyester

Weight 260 g/m²

Width 140 cm

Fabric direction Standard Direction

Fitting ↔ 0.0 cm ↓ 0.0 cm

Maintenance advice     

Label OEKO-TEX STANDARD 100

Minimum order 25 linear(s) meter(s)



Visual not taking into account the printing medium, the final rendering may vary according to the chosen medium.


Technical characteristics

Flame retardant	NF 12952	
Acoustic	Noise reduction coefficient (NRC) :	0.88
Resilience	Dimensional Stability (%)	
	Warp	0
	Weft	0
	Breaking Elongation	
	Warp	17
	Weft	27
Resilience	Breaking load (daN)	
	Warp	87
	Weft	110


Print pattern SALIN




SALIN Abricot 08



SALIN Anis 62




SALIN Fuchsia 33




SALIN Naturel 26




SALIN Océan 91



SALIN Orange 15



SALIN Rouge 21



SALIN Turquoise 53