



BELORA BPI 00
Printing support



SCOURTIN Céladon 135
Print pattern

Printing support **BELORA BPI 00** Print pattern **SCOURTIN Céladon 135**

Dimout support for digital printing. It does not have an M1 fire rating.

Technical properties



Flame retardant



Thermal



Acoustic

Applications Roman blinds - Panel curtains - Lining - Curtains

Composition 100% polyester

Weight 260 g/m²

Width 140 cm

Fabric direction Standard Direction

Fitting ↔ cm ↓ cm

Maintenance advice

Label OEKO-TEX STANDARD 100

Minimum order 25 linear(s) meter(s)



Visual not taking into account the printing medium, the final rendering may vary according to the chosen medium.

Technical characteristics

Flame retardant	NF 12952	
Acoustic	Noise reduction coefficient (NRC) :	0.88
Resilience	Dimensional Stability (%)	
	Warp	0
	Weft	0
	Breaking Elongation	
	Warp	17
	Weft	27
	Breaking load (daN)	
	Warp	87
	Weft	110

Print pattern SCOURTIN



SCOURTIN Beige 63




SCOURTIN Fuchsia 33




SCOURTIN Sapin 126




SCOURTIN Bergamote
121



SCOURTIN Anthracite
38




SCOURTIN Violine 105




SCOURTIN Pacifique 54




SCOURTIN Rose 129



SCOURTIN Blanc 01




SCOURTIN Lin 11



SCOURTIN Naturel 26




SCOURTIN Citrouille
136



SCOURTIN Turquoise 53




SCOURTIN Brun 23




SCOURTIN Hortensia
134




SCOURTIN Orage 123



SCOURTIN Rubis 59



SCOURTIN Ficelle 09



SCOURTIN Maïs 37



SCOURTIN Ebene 113

drapilux
By Sotexpro

DRAPILUX GmbH - Hofenstraße 3, 77694 Kehl - Deutschland

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected

Print pattern SCOURTIN



SCOURTIN Tourterelle
138



SCOURTIN Titanium 98



SCOURTIN Lagon 110



SCOURTIN Gris 97