


BOREAL BPI 00
Printing support



SONG Opéra 104
Print pattern



Printing support **BOREAL BPI 00** Print pattern **SONG Opéra 104**

Dimout support for digital printing

Technical properties



Flame retardant



Thermal



Acoustic

Applications Roman blinds - Valences - Lining - Bed runners - Curtains

Composition 100% FR polyester

Weight 260 g/m²

Width 145 cm

Fabric direction Standard Direction

Fitting ↔ 35.0 cm ↓ 35.0 cm

Maintenance advice     

Label OEKO-TEX STANDARD 100

Minimum order 25 linear(s) meter(s)




Visual not taking into account the printing medium, the final rendering may vary according to the chosen medium.


Technical characteristics

Flame retardant	M1 / B1 / IMO PASS / UNI 8456 / 9174 Classe Uno	
Acoustic	Noise reduction coefficient (NRC) :	0.88
Resilience	Dimentional Stability (%)	
	Warp	0
	Weft	0
	Breaking Elongation	
	Warp	17
	Weft	27
	Breaking load (daN)	
	Warp	87
	Weft	110


Print pattern SONG




SONG Agrume 69




SONG Framboise 81




SONG Lierre 124




SONG Menthe 122




SONG Naturel 26




SONG Navy 120




SONG Océan 91



SONG Orage 123




SONG Orange 15




SONG Prairie 125




SONG Prune 84




SONG Sanguine 05




SONG Soleil 127




SONG Titanium 98



SONG Violine 105




SONG Jade 116



SONG Sapin 126



SONG Tilleul 103



SONG maïs 37

drapilux
By Sotexpro

DRAPILUX GmbH - Hafenstraße 3, 77694 Kehl - Deutschland

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected