



# BORNEO BPI 00

## Technical properties



Flame retardant



Thermal



Acoustic

Applications Roman blinds - Curtains

Composition 100% FR polyester

Weight 440 g/m<sup>2</sup> Width 280 cm

Fabric direction Room high or standard direction Fitting ↔ cm ↓ cm

Maintenance advice    

Certifications OEKO-TEX STANDARD 100 (CQ 1006/1)

Minimum order 25 linear(s) meter(s)

## Technical characteristics

Flame retardant	M1 / B1 / IMO PASS / UNI 8456 / 9174 Classe Uno	
Acoustic	Noise reduction coefficient (NRC) :	<b>0.89</b>
	Weighted sound absorption coefficient (a <sub>w</sub> ) :	<b>0.90</b>
	Acoustic absorption class (a <sub>w</sub> ) :	<b>A</b>
Optical index	Light reflexion :	<b>60 %</b>
	Light absorption :	<b>40 %</b>
	Light transmission :	<b>0 %</b>
Thermal index	Solar reflexion :	<b>56 %</b>
	Solar absorption :	<b>44 %</b>
	Solar transmission :	<b>0 %</b>
	UV transmission :	<b>0 %</b>
	Gtot :	<b>Gt 39 % Fc 65 %</b>
Resilience	Lightfastness (units Class/8)	<b>6</b>
	Dimensional Stability (%)	
	Warp	<b>-0.5</b>
	Weft	<b>0</b>
	Breaking Elongation	
	Warp	<b>31</b>
	Weft	<b>0</b>
	Breaking load (daN)	
	Warp	<b>130</b>
	Weft	<b>250</b>

**drapilux**  
By Sotexpro

DRAPILUX GmbH - Hafenstraße 3, 77694 Kehl - Deutschland

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected