



COLLEGE Titanium 98

This light-filtering fabric is available in a range of several colours, providing you with some great decoration possibilities.

Technical properties



Flame retardant



Thermal

Applications Roman blinds - Panel curtains - Curtains - Decorative frames

Composition 100% FR polyester

Weight 200 g/m² Width 140 cm / 280 cm

Fabric direction Room high or standard direction Fitting ↔ cm ↓ cm

Maintenance advice     

Labels France Terre Textile (R016)

Certifications OEKO-TEX STANDARD 100 (CQ 1006/1)

Minimum order 1 linear(s) meter(s)

Technical characteristics

Flame retardant

M1 / EN13773 : 2003 Class 1 / B1 / IMO PASS / UNI 8456 / 9174
Classe Uno

Optical index

Light reflexion :	2 %
Light absorption :	93 %
Light transmission :	5 %

Thermal index

Solar reflexion :	28 %
Solar absorption :	53 %
Solar transmission :	19 %
UV transmission :	5 %
Gtot :	Gt 48 % Fc 81 %

Resilience

Lightfastness (units Class/8)	4
Dimensional Stability (%)	
Warp	-2.5
Weft	-0.5
Breaking Elongation	
Warp	23
Weft	24
Breaking load (daN)	
Warp	93
Weft	120

drapilux
By Sotexpro

DRAPILUX GmbH - Hafenstraße 3, 77694 Kehl - Deutschland

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected