

# CORTE Moka 13

This plain light-filtering fabric is available in several colours.

## Technical properties



Flame retardant



Thermal








Acoustic

**Applications** Roman blinds - Panel curtains - Bedspreads - Valences - Seating - Bed runners - Curtains - Cushions - Decorative frames

**Composition** 100% FR polyester

**Weight** 230 g/m<sup>2</sup> **Width** 140 cm / 280 cm

**Fabric direction** Room high or standard direction **Fitting** ↔ cm ↓ cm

**Maintenance advice**     

**Labels** France Terre Textile (R016)

**Certifications** OEKO-TEX STANDARD 100 (CQ 1006/1)

**Minimum order** 1 linear(s) meter(s)

## Technical characteristics

Flame retardant	M1 / BS 5867 TYPE C / B1 / IMO PASS / UNI 8456 / 9174 Classe Uno
Acoustic	<p>Noise reduction coefficient (NRC) : <b>0.90</b></p> <p>Weighted sound absorption coefficient (a<sub>w</sub>) : <b>0.85</b></p> <p>Acoustic absorption class (a<sub>w</sub>) : <b>B</b></p>
Optical index	<p>Light reflexion : <b>36 %</b></p> <p>Light absorption : <b>58 %</b></p> <p>Light transmission : <b>6 %</b></p>
Thermal index	<p>Solar reflexion : <b>50 %</b></p> <p>Solar absorption : <b>33 %</b></p> <p>Solar transmission : <b>17 %</b></p> <p>UV transmission : <b>-2 %</b></p> <p>Gtot : <b>Gt 41 % Fc 69 %</b></p>
Resilience	<p>Lightfastness (units Class/8) <b>5</b></p> <p>Pilling <b>4</b></p> <p>Dimensional Stability (%)</p> <p>    Warp <b>-2</b></p> <p>    Weft <b>-0.5</b></p> <p>Martindale (Cycles) <b>24998</b></p> <p>Breaking Elongation</p> <p>    Warp <b>34</b></p> <p>    Weft <b>28</b></p> <p>Breaking load (daN)</p> <p>    Warp <b>130</b></p> <p>    Weft <b>90</b></p>