



CORTE Ocre 03

This plain light-filtering fabric is available in several colours.

Technical properties



Flame retardant



Thermal



Acoustic

Applications Roman blinds - Panel curtains - Bedspreads - Valences - Seating - Bed runners - Curtains - Cushions - Decorative frames

Composition 100% FR polyester

Weight 230 g/m² **Width** 140 cm / 280 cm

Fabric direction Room high or standard direction **Fitting** ↔ cm ↓ cm

Maintenance advice

Labels France Terre Textile (R016)

Certifications OEKO-TEX STANDARD 100 (CQ 1006/1)

Minimum order 1 linear(s) meter(s)

Technical characteristics

Flame retardant	M1 / BS 5867 TYPE C / B1 / IMO PASS / UNI 8456 / 9174 Classe Uno
Acoustic	Noise reduction coefficient (NRC) : 0.90 Weighted sound absorption coefficient (a _w) : 0.85 Acoustic absorption class (a _w) : B
Optical index	Light reflexion : 36 % Light absorption : 58 % Light transmission : 6 %
Thermal index	Solar reflexion : 50 % Solar absorption : 33 % Solar transmission : 17 % UV transmission : 0 % Gtot : Gt 41 % Fc 69 %
Resilience	Lightfastness (units Class/8) 5 Pilling 4 Dimensional Stability (%) Warp -2 Weft -0.5 Martindale (Cycles) 25000 Breaking Elongation Warp 34 Weft 28 Breaking load (daN) Warp 130 Weft 90



DRAPILUX GmbH - Hafenstraße 3, 77694 Kehl - Deutschland

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected