




LY Blanc 01
Printing support



ONDES Anis 62
Print pattern



Printing support **LY Blanc 01** Print pattern **ONDES Anis 62**

Fine linen look sheer. The weaving of the LY is slightly textured which allows it to be easily printed by sublimation

Technical properties



Flame retardant Transparent

Applications Roman blinds - Panel curtains - Curtains

Composition 100% polyester/polyester FR

Weight 90 g/m²

Width 290 cm

Fabric direction Room High Direction

Fitting ↔ 25.0 cm ↓ 20.0 cm

Maintenance advice     

Label France Terre Textile / OEKO-TEX STANDARD 100

Minimum order 25 linear(s) meter(s)



Visual not taking into account the printing medium, the final rendering may vary according to the chosen medium.


Technical characteristics

Flame retardant	M1 / B1 / IMO PASS		
Optical index	Light reflexion :	33 %	
	Light absorption :	2 %	
	Light transmission :	65 %	
Transparent veil	Yes		
Thermal index	Solar reflexion :	32 %	
	Solar absorption :	4 %	
	Solar transmission :	64 %	
	UV transmission :	50 %	
	Gtot :	Gt 48 % Fc 81 %	
Resilience	Lightfastness (units Class/8)	6	
	Dimensional Stability (%)	Warp	0
		Weft	0
	Breaking Elongation	Warp	69
		Weft	58
	Breaking load (daN)	Warp	47
		Weft	24


Print pattern ONDES




ONDES Opéra 104



ONDES Turquoise 53



ONDES Violine 105



ONDES glacier 43

drapilux
By Sotexpro

DRAPILUX GmbH - Hafenstraße 3, 77694 Kehl - Deutschland

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected