



LY Blanc 01
Printing support



SONG Violine 105
Print pattern



Printing support **LY Blanc 01** Print pattern **SONG Violine 105**

Fine linen look sheer. The weaving of the LY is slightly textured which allows it to be easily printed by sublimation

Technical properties



Flame retardant Transparent

Applications Roman blinds - Panel curtains - Curtains

Composition 100% polyester/polyester FR

Weight 90 g/m²

Width 290 cm

Fabric direction Room High Direction

Fitting ↔ 35.0 cm ↓ 35.0 cm

Maintenance advice     

Label France Terre Textile / OEKO-TEX STANDARD 100

Minimum order 25 linear(s) meter(s)



Visual not taking into account the printing medium, the final rendering may vary according to the chosen medium.

Technical characteristics

| | | |
|------------------|-------------------------------|-----------------|
| Flame retardant | M1 / B1 / IMO PASS | |
| Optical index | Light reflexion : | 33 % |
| | Light absorption : | 2 % |
| | Light transmission : | 65 % |
| Transparent veil | Yes | |
| Thermal index | Solar reflexion : | 32 % |
| | Solar absorption : | 4 % |
| | Solar transmission : | 64 % |
| | UV transmission : | 50 % |
| | Gtot : | Gt 48 % Fc 81 % |
| Resilience | Lightfastness (units Class/8) | 6 |
| | Dimensional Stability (%) | |
| | Warp | 0 |
| | Weft | 0 |
| | Breaking Elongation | |
| | Warp | 69 |
| | Weft | 58 |
| | Breaking load (daN) | |
| | Warp | 47 |
| Weft | 24 | |

Print pattern SONG



SONG Opéra 104



SONG Agrume 69



SONG Framboise 81



SONG Lierre 124



SONG Menthe 122



SONG Naturel 26



SONG Navy 120



SONG Océan 91



SONG Orage 123



SONG Orange 15



SONG Prairie 125



SONG Prune 84



SONG Sanguine 05



SONG Soleil 127



SONG Titanium 98



SONG Jade 116



SONG Sapin 126



SONG Tilleul 103



SONG maïs 37

drapilux
By Sotexpro

DRAPILUX GmbH - Hafenstraße 3, 77694 Kehl - Deutschland

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected