



LY BPI 00  
Printing support



PAOLO Azur 137  
Print pattern



## Printing support LY BPI 00 Print pattern PAOLO Azur 137

Fine linen look sheer. The weaving of the LY is slightly textured which allows it to be easily printed by sublimation

### Technical properties



Flame retardant    Transparent

**Applications** Roman blinds - Panel curtains - Curtains

**Composition** 100% polyester/polyester FR

**Weight** 90 g/m<sup>2</sup>

**Width** 290 cm

**Fabric direction** Room High Direction

**Fitting** ↔ 24.0 cm ↓ 30.0 cm

**Maintenance advice**     

**Label** France Terre Textile / OEKO-TEX STANDARD 100

**Minimum order** 25 linear(s) meter(s)



Visual not taking into account the printing medium, the final rendering may vary according to the chosen medium.

## Technical characteristics

Flame retardant	M1 / B1 / IMO PASS																				
Transparent veil	Yes																				
Resilience	<table border="0"> <tr> <td>Lightfastness (units Class/8)</td> <td>6</td> </tr> <tr> <td>Dimensional Stability (%)</td> <td></td> </tr> <tr> <td>    Warp</td> <td>0</td> </tr> <tr> <td>    Weft</td> <td>0</td> </tr> <tr> <td>Breaking Elongation</td> <td></td> </tr> <tr> <td>    Warp</td> <td>69</td> </tr> <tr> <td>    Weft</td> <td>58</td> </tr> <tr> <td>Breaking load (daN)</td> <td></td> </tr> <tr> <td>    Warp</td> <td>47</td> </tr> <tr> <td>    Weft</td> <td>24</td> </tr> </table>	Lightfastness (units Class/8)	6	Dimensional Stability (%)		Warp	0	Weft	0	Breaking Elongation		Warp	69	Weft	58	Breaking load (daN)		Warp	47	Weft	24
Lightfastness (units Class/8)	6																				
Dimensional Stability (%)																					
Warp	0																				
Weft	0																				
Breaking Elongation																					
Warp	69																				
Weft	58																				
Breaking load (daN)																					
Warp	47																				
Weft	24																				

# Print pattern PAOLO



PAOLO Ficelle 09