



MIRAGE 2 Anthracite 38

This plain fabric with aluminised backing is perfect for sunlight protection, Fabric cannot be installed in wet areas. Dry cleaning required. Please note: this fabric is not suitable for horizontal installation.

Technical properties

Flame retardant Thermal

Applications Roman blinds - Roller blinds - Panel curtains - Curtains

Composition 100% Aluminized Polyester

Weight 200 g/m² **Width** 280 cm

Fabric direction Room high or standard direction **Fitting** ↔ cm ↕ cm

Maintenance advice

Minimum order 1 linear(s) metter(s)

Technical characteristics

Flame retardant	M1 / IMO PASS	
Optical index	Light reflexion :	**55 %**
	Light absorption :	**38 %**
	Light transmission :	**7 %**
Thermal index	Solar reflexion :	**56 %**
	Solar absorption :	**37 %**
	Solar transmission :	**7 %**
	UV transmission :	**5 %**
	Gtot :	**Gt 39 % Fc 66 %**
Resilience	Lightfastness (units Class/8)	**6**
	Dimentional Stability (%)	
	Warp	**0**
	Weft	**-0.5**
	Breaking Elongation	
	Warp	**25**
	Weft	**23**
	Breaking load (daN)	
	Warp	**110**
	Weft	**140**