



MIRAGE 2 Crème 02

This plain fabric with aluminised backing is perfect for sunlight protection, Fabric cannot be installed in wet areas. Dry cleaning required. Please note: this fabric is not suitable for horizontal installation.

Technical properties



Flame retardant



Thermal

Applications Roman blinds - Roller blinds - Panel curtains - Curtains

Composition 100% Aluminized Polyester

Weight 200 g/m² **Width** 280 cm

Fabric direction Room high or standard direction **Fitting** ↔ cm ↓ cm

Maintenance advice ☒ ☒ ☒ ☒ ☒ ☒

Minimum order 1 linear(s) meter(s)

Technical characteristics

| | | |
|-----------------|-------------------------------|-----------------|
| Flame retardant | M1 / IMO PASS | |
| Optical index | Light reflexion : | 55 % |
| | Light absorption : | 38 % |
| | Light transmission : | 7 % |
| Thermal index | Solar reflexion : | 56 % |
| | Solar absorption : | 37 % |
| | Solar transmission : | 7 % |
| | UV transmission : | 5 % |
| | Gtot : | Gt 39 % Fc 66 % |
| Resilience | Lightfastness (units Class/8) | 6 |
| | Dimensional Stability (%) | |
| | Warp | 0 |
| | Weft | -0.5 |
| | Breaking Elongation | |
| | Warp | 25 |
| | Weft | 23 |
| | Breaking load (daN) | |
| | Warp | 110 |
| Weft | 140 | |

drapilux
By Sotexpro

DRAPILUX GmbH - Hafenstraße 3, 77694 Kehl - Deutschland

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected