



# MIRAGE 2 Sienne 29

This plain fabric with aluminised backing is perfect for sunlight protection, Fabric cannot be installed in wet areas. Dry cleaning required. Please note: this fabric is not suitable for horizontal installation.

## Technical properties



Flame retardant



Thermal

**Applications** Roman blinds - Roller blinds - Panel curtains - Curtains

**Composition** 100% Aluminized Polyester

**Weight** 200 g/m<sup>2</sup> **Width** 280 cm

**Fabric direction** Room high or standard direction **Fitting** ↔ cm ↓ cm

**Maintenance advice** ☒ ☒ ☒ ☒

**Minimum order** 1 linear(s) meter(s)

## Technical characteristics

Flame retardant	M1 / IMO PASS
Optical index	Light reflexion : <b>55 %</b>
	Light absorption : <b>38 %</b>
	Light transmission : <b>7 %</b>
Thermal index	Solar reflexion : <b>56 %</b>
	Solar absorption : <b>37 %</b>
	Solar transmission : <b>7 %</b>
	UV transmission : <b>5 %</b>
	Gtot : <b>Gt 39 % Fc 66 %</b>
Resilience	Lightfastness (units Class/8) <b>6</b>
	Dimensional Stability (%)
	Warp <b>0</b>
	Weft <b>-0.5</b>
	Breaking Elongation
	Warp <b>25</b>
	Weft <b>23</b>
	Breaking load (daN)
	Warp <b>110</b>
Weft <b>140</b>	