



**NATTE bpi 00**  
Printing support



**6105 Beige 63**  
Print pattern

## Printing support **NATTE bpi 00** Print pattern **6105 Beige 63**

This light-filtering fabric serves as a print medium.

### Technical properties



Flame retardant

**Applications** Roman blinds - Panel curtains - Bedspreads - Valences - Bed runners  
- Curtains - Cushions

**Composition** 100% FR polyester

**Weight** 230 g/m<sup>2</sup>

**Width** 140 cm

**Fabric direction** Standard Direction

**Fitting** ↔ 81.0 cm ↓ 95.0 cm

**Maintenance advice**     

**Label** France Terre Textile / OEKO-TEX STANDARD 100

**Minimum order** 25 linear(s) meter(s)



Visual not taking into account the printing medium, the final rendering may vary according to the chosen medium.

## Technical characteristics

|                           |                                     |                               |
|---------------------------|-------------------------------------|-------------------------------|
| Flame retardant           | M1 / IMO PASS                       |                               |
| Acoustic                  | Noise reduction coefficient (NRC) : | <b>0.90</b>                   |
| Optical index             | Light reflexion :                   | <b>5 %</b>                    |
|                           | Light absorption :                  | <b>94 %</b>                   |
|                           | Light transmission :                | <b>1 %</b>                    |
| Thermal index             | Solar reflexion :                   | <b>39 %</b>                   |
|                           | Solar absorption :                  | <b>48 %</b>                   |
|                           | Solar transmission :                | <b>13 %</b>                   |
|                           | UV transmission :                   | <b>0 %</b>                    |
|                           | Gtot :                              | <b>Gt 48 % Fc 69 %</b>        |
|                           | Resilience                          | Lightfastness (units Class/8) |
| Pilling                   |                                     | <b>5</b>                      |
| Dimensional Stability (%) |                                     |                               |
| Warp                      |                                     | <b>-2</b>                     |
| Weft                      |                                     | <b>-1</b>                     |
| Martindale (Cycles)       |                                     | <b>40000</b>                  |
| Breaking Elongation       |                                     |                               |
| Warp                      |                                     | <b>38</b>                     |
| Weft                      |                                     | <b>21</b>                     |
| Breaking load (daN)       |                                     |                               |
| Warp                      |                                     | <b>150</b>                    |
| Weft                      |                                     | <b>93</b>                     |