




**NOCLIN NATUREL 26**  
Printing support



**SONG Soleil 127**  
Print pattern



Visual not taking into account the printing medium, the final rendering may vary according to the chosen medium.

## Printing support **NOCLIN NATUREL 26**

### Print pattern **SONG Soleil 127**

Blackout double-side, linen and textured effect, the Noclin is also available as a printing support, to bring depth and relief to your patterns, please note : the beige background may modify the final appearance.

#### Technical properties



Flame retardant



Thermal

**Applications** Roman blinds - Panel curtains - Curtains

**Composition** Polyester enduction acrylique

**Weight** 380 g/m<sup>2</sup>

**Width** 280 cm

**Fabric direction** Room High Direction

**Fitting** ↔ 35.0 cm ↓ 35.0 cm

**Maintenance advice**    

**Label**

**Minimum order** 25 linear(s) metter(s)

## Technical characteristics

Flame retardant	B1 / IMO PASS		
Optical index	Light reflexion :	53 %	
	Light absorption :	47 %	
	Light transmission :	0 %	
Thermal index	Solar reflexion :	64 %	
	Solar absorption :	36 %	
	Solar transmission :	0 %	
	UV transmission :	0 %	
	Gtot :	Gt 36 % Fc 61 %	
	Resilience	Lightfastness (units Class/8)	4
Dimensional Stability (%)		Warp	-1
		Weft	-1
Breaking Elongation		Warp	48
		Weft	72
Breaking load (daN)		Warp	51
		Weft	84

# Print pattern SONG



SONG Opéra 104



SONG Agrume 69



SONG Framboise 81



SONG Lierre 124



SONG Menthe 122



SONG Naturel 26



SONG Navy 120



SONG Océan 91



SONG Orage 123



SONG Orange 15



SONG Prairie 125



SONG Prune 84



SONG Sanguine 05



SONG Titanium 98



SONG Violine 105



SONG Jade 116



SONG Sapin 126



SONG Tilleul 103



SONG maïs 37

**drapilux**  
By Sotexpro

DRAPILUX GmbH - Hafenstraße 3, 77694 Kehl - Deutschland

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected