




NOCLIN NATUREL 26
Printing support



TUMULTE Menthe 122
Print pattern



Visual not taking into account the printing medium, the final rendering may vary according to the chosen medium.

Printing support **NOCLIN NATUREL 26**

Print pattern **TUMULTE Menthe 122**

Blackout double-side, linen and textured effect, the Noclin is also available as a printing support, to bring depth and relief to your patterns, please note : the beige background may modify the final appearance.

Technical properties



Flame retardant



Thermal

Applications Roman blinds - Panel curtains - Curtains

Composition Polyester enduction acrylique

Weight 380 g/m²

Width 280 cm

Fabric direction Room High Direction

Fitting ↔ 17.0 cm ↓ 15.0 cm

Maintenance advice    

Label

Minimum order 25 linear(s) metter(s)

Technical characteristics

| | | |
|---------------------|-------------------------------|------------------------|
| Flame retardant | B1 / IMO PASS | |
| Optical index | Light reflexion : | 53 % |
| | Light absorption : | 47 % |
| | Light transmission : | 0 % |
| Thermal index | Solar reflexion : | 64 % |
| | Solar absorption : | 36 % |
| | Solar transmission : | 0 % |
| | UV transmission : | 0 % |
| | Gtot : | Gt 36 % Fc 61 % |
| Resilience | Lightfastness (units Class/8) | 4 |
| | Dimensional Stability (%) | |
| | Warp | -1 |
| | Weft | -1 |
| | Breaking Elongation | |
| | Warp | 48 |
| | Weft | 72 |
| Breaking load (daN) | | |
| Warp | 51 | |
| Weft | 84 | |

Print pattern TUMULTE



TUMULTE Lilas 19



TUMULTE Maïs 37



TUMULTE Orage 123



TUMULTE Prairie 125



TUMULTE Safran 49