


**NOCLIN NATUREL 26**  
Printing support



**PUNSIKA OCRE 03**  
Print pattern

## Printing support **NOCLIN NATUREL 26**

### Print pattern **PUNSIKA OCRE 03**

Blackout double-side, linen and textured effect, the Noclin is also available as a printing support, to bring depth and relief to your patterns, please note : the beige background may modify the final appearance.

#### Technical properties



Flame retardant



Thermal

**Applications** Roman blinds - Panel curtains - Curtains

**Composition** Polyester enduction acrylique

**Weight** 380 g/m<sup>2</sup>

**Width** 280 cm

**Fabric direction** Room High Direction

**Fitting** ↔ 68.0 cm ↓ 51.0 cm

**Maintenance advice**    

**Label**

**Minimum order** 25 linear(s) meter(s)



Visual not taking into account the printing medium, the final rendering may vary according to the chosen medium.

## Technical characteristics

Flame retardant

B1 / IMO PASS

Optical index

Light reflexion : **53 %**

Light absorption : **47 %**

Light transmission : **0 %**

Thermal index

Solar reflexion : **64 %**

Solar absorption : **36 %**

Solar transmission : **0 %**

UV transmission : **0 %**

Gtot : **Gt 36 % Fc 61 %**

Resilience

Lightfastness (units Class/8) **4**

Dimentional Stability (%)

Warp **-1**

Weft **-1**

Breaking Elongation

Warp **48**


Weft **72**

Breaking load (daN)

Warp **51**

Weft **84**

# Print pattern PUNSIKA



PUNSIKA CHATAIGNE  
55