



NOCTEA BPI 00
Printing support



SABLE Lin 11
Print pattern



Printing support **NOCTEA BPI 00** Print pattern **SABLE Lin 11**

This fabric is used as a print medium.

Technical properties



Flame retardant

Applications Roman blinds - Roller blinds - Panel curtains - Lining - Curtains

Composition 100% polyester with white flocked acrylic backing

Weight 310 g/m²

Width 280 cm

Fabric direction Room High Direction

Fitting ↔ 0.0 cm ↓ 0.0 cm

Maintenance advice

Label

Minimum order 25 linear(s) meter(s)



Visual not taking into account the printing medium, the final rendering may vary according to the chosen medium.

Technical characteristics

Flame retardant	M1 / BS 5867 TYPE C / B1 / IMO PASS	
Optical index	Light reflexion : 71 %	
	Light absorption : 29 %	
	Light transmission : 0 %	
Thermal index	Solar reflexion : 66 %	
	Solar absorption : 34 %	
	Solar transmission : 0 %	
	UV transmission : 0 %	
	Gtot :	Gt 35 % Fc 60 %
	Resilience	Lightfastness (units Class/8) 4
	Dimensional Stability (%)	
	Warp -0,5	
	Weft 0	
	Breaking Elongation	
	Warp 19	
	Weft 22	
	Breaking load (daN)	
	Warp 37	
	Weft 57	

Print pattern SABLE



SABLE Rose 129



SABLE Sable 67



SABLE Absinthe 132



SABLE Ivoire 115



SABLE Noir 10



SABLE Souris 31



SABLE Gris 97



SABLE Jasmin 74

drapilux
By Sotexpro

DRAPILUX GmbH - Hafenstraße 3, 77694 Kehl - Deutschland

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected