




**NOCTIS BPI 00**  
Printing support



**PEKKA Anis 62**  
Print pattern



## Printing support **NOCTIS BPI 00** Print pattern **PEKKA Anis 62**

This fabric is used as a print medium.

### Technical properties



Flame retardant

**Applications** Roman blinds - Roller blinds - Panel curtains - Lining - Curtains

**Composition** 100% polyester with white flocked acrylic backing

**Weight** 290 g/m<sup>2</sup>

**Width** 140 cm

**Fabric direction** Standard Direction

**Fitting** ↔ 18.0 cm ↓ 6.0 cm

**Maintenance advice**

**Label**

**Minimum order** 5 linear(s) metter(s)



Visual not taking into account the printing medium, the final rendering may vary according to the chosen medium.

## Technical characteristics

Flame retardant	M1	
Acoustic	Noise reduction coefficient (NRC) :	<b>0.28</b>
Optical index	Light reflexion :	<b>71 %</b>
	Light absorption :	<b>29 %</b>
	Light transmission :	<b>0 %</b>
Thermal index	Solar reflexion :	<b>64 %</b>
	Solar absorption :	<b>36 %</b>
	Solar transmission :	<b>0 %</b>
	UV transmission :	<b>0 %</b>
	Gtot :	<b>Gt 36 % Fc 61 %</b>
Resilience	Lightfastness (units Class/8)	<b>6</b>
	Dimensional Stability (%)	
	Warp	<b>-0,5</b>
	Weft	<b>0</b>
	Breaking Elongation	
	Warp	<b>20</b>
	Weft	<b>24</b>
	Breaking load (daN)	
	Warp	<b>53</b>
Weft	<b>63</b>	

## Print pattern PEKKA



PEKKA Grenat 56



PEKKA Orange 15



PEKKA Turquoise 53



PEKKA cactus 36