



NOCTURNE Grisé 03

This plain fabric blocks out light very effectively and is available in a wide variety of colours.

Technical properties



Flame retardant



Thermal

Applications Roman blinds - Panel curtains - Lining - Curtains

Composition 100% polyester with white flocked acrylic backing

Weight 280 g/m² 784 g/ml Width 280 cm

Fabric direction Room high or standard direction Fitting ↔ cm ↓ cm

Maintenance advice

Minimum order 1 linear(s) meter(s)

Technical characteristics

| | | | |
|-----------------|-------------------------------------|-----------------|------|
| Flame retardant | M1 / BS 5867 TYPE C / B1 / IMO PASS | | |
| Optical index | Light reflexion : | 71 % | |
| | Light absorption : | 29 % | |
| | Light transmission : | 0 % | |
| Thermal index | Solar reflexion : | 66 % | |
| | Solar absorption : | 34 % | |
| | Solar transmission : | 0 % | |
| | UV transmission : | 0 % | |
| | Gtot : | Gt 35 % Fc 60 % | |
| Resilience | Lightfastness (units Class/8) | 4 | |
| | Pilling | 3-4 | |
| | Dimentional Stability (%) | Warp | -0,5 |
| | | Weft | 0 |
| | Martindale (Cycles) | 40000 | |
| | Breaking Elongation | Warp | 19 |
| | | Weft | 22 |
| | Breaking load (daN) | Warp | 37 |
| | | Weft | 57 |