



**NOCTWIN BPI 00**  
Printing support



**TULIPE Nuit 128**  
Print pattern



Visual not taking into account the printing medium, the final rendering may vary according to the chosen medium.

## Printing support **NOCTWIN BPI 00** Print pattern **TULIPE Nuit 128**

Support occultant pour impression, imprimable des 2 côtés.

### Technical properties



Flame retardant

**Applications** Roman blinds - Panel curtains - Curtains

**Composition** Polyester/acrylique envers floqué

**Weight** 300 g/m<sup>2</sup>

**Width** 280 cm

**Fabric direction** Room High Direction

**Fitting** ↔ 23.0 cm ↓ 28.0 cm

**Maintenance advice**     

**Label**

**Minimum order** 25 linear(s) meter(s)

## Technical characteristics

Flame retardant

B1 / IMO PASS

Resilience

Lightfastness (units Class/8)	<b>6</b>
Dimensional Stability (%)	
Warp	<b>-1</b>
Weft	<b>0</b>
Breaking Elongation	
Warp	<b>31</b>
Weft	<b>8</b>
Breaking load (daN)	
Warp	<b>120</b>
Weft	<b>43</b>

# Print pattern TULIPE



TULIPE Lierre 124



TULIPE Rose 129



TULIPE Soleil 127



TULIPE Anis 62



TULIPE Bordeaux 04



TULIPE Indigo 119