



**OPAQ BPI 00**  
Printing support



**ELAINA Lin 11**  
Print pattern



## Printing support **OPAQ BPI 00** Print pattern **ELAINA Lin 11**

Unclassified blackout print support

### Technical properties

**Applications** Roman blinds - Panel curtains - Lining - Curtains

**Composition** 100% polyester with white flocked acrylic backing

**Weight** 280 g/m<sup>2</sup>

**Width** 280 cm

**Fabric direction** Room High Direction

**Fitting** ↔ 0.0 cm ↑ 0.0 cm

**Maintenance advice**     

**Label**

**Minimum order** 25 linear(s) meter(s)



Visual not taking into account the printing medium, the final rendering may vary according to the chosen medium.

## Technical characteristics

|                     |                               |                        |
|---------------------|-------------------------------|------------------------|
| Optical index       | Light reflexion :             | <b>82 %</b>            |
|                     | Light absorption :            | <b>18 %</b>            |
|                     | Light transmission :          | <b>0 %</b>             |
| Thermal index       | Solar reflexion :             | <b>74 %</b>            |
|                     | Solar absorption :            | <b>26 %</b>            |
|                     | Solar transmission :          | <b>0 %</b>             |
|                     | UV transmission :             | <b>0 %</b>             |
|                     | Gtot :                        | <b>Gt 33 % Fc 55 %</b> |
| Resilience          | Lightfastness (units Class/8) | <b>5</b>               |
|                     | Dimensional Stability (%)     |                        |
|                     | Warp                          | <b>-0,5</b>            |
|                     | Weft                          | <b>0</b>               |
|                     | Breaking Elongation           |                        |
|                     | Warp                          | <b>26</b>              |
|                     | Weft                          | <b>15</b>              |
| Breaking load (daN) |                               |                        |
| Warp                | <b>62</b>                     |                        |
| Weft                | <b>31</b>                     |                        |

# Print pattern ELAINA



ELAINA Gris 91



ELAINA Violine 105



ELAINA Ocre 03



ELAINA Bergamote 121



ELAINA Rose 129



ELAINA Pacifique 54



ELAINA Beige 63



ELAINA Céladon 135



ELAINA Saphir 106



ELAINA Anis 62



ELAINA Rouge 21



ELAINA Hortensia 134



ELAINA Prairie 125



ELAINA Graphite 77



ELAINA Lierre 124



ELAINA Naturel 26



ELAINA Genêt 06



ELAINA Ivoire 115



ELAINA Gentiane 16



ELAINA Navy 120

**drapilux**  
By Sotexpro

DRAPILUX GmbH - Hofenstraße 3, 77694 Kehl - Deutschland

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected

## Print pattern ELAINA



ELAINA Chamois 111



ELAINA Turquoise 53



ELAINA Anthracite 38



ELAINA Fiesta 131

**drapilux**  
By Sotexpro

DRAPILUX GmbH - Hafenstraße 3, 77694 Kehl - Deutschland

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected