

# SIENTO LITO Taupe 95

Light-filtering fabric made from recycled yarns. The proportion of recycled material and the manufacturing process of the yarn used to weave this quality can cause slight color variations between different batches of fabric.

## Technical properties



Flame retardant








Recycled fabrics

**Applications** Roman blinds - Panel curtains - Curtains - Decorative frames

**Composition** 100% FR polyester including 90% recycled material

**Weight** 335 g/m<sup>2</sup> **Width** 280 cm

**Fabric direction** Room High Direction **Fitting** ↔ cm ↓ cm

**Maintenance advice**     

**Labels** France Terre Textile (R016)

**Certifications** OEKO-TEX STANDARD 100 Recyclé (CQ 1006/2)

**Minimum order** 1 linear(s) meter(s)

## Technical characteristics

Flame retardant	M1 / B1 / IMO PASS / UNI 8456 / 9174 Classe Uno	
Acoustic	Noise reduction coefficient (NRC) :	<b>0.76</b>
	Weighted sound absorption coefficient (a <sub>w</sub> ) :	<b>0.70</b>
	Acoustic absorption class (a <sub>w</sub> ) :	<b>C</b>
Resilience	Lightfastness (units Class/8)	<b>5</b>
	Pilling	<b>1</b>
	Dimensional Stability (%)	
	Warp	<b>-1</b>
	Weft	<b>-0.5</b>
	Martindale (Cycles)	<b>20000</b>
	Breaking Elongation	
	Warp	<b>49</b>
	Weft	<b>34</b>
	Breaking load (daN)	
Warp	<b>140</b>	
Weft	<b>79</b>	

**drapilux**  
By Sotexpro

DRAPILUX GmbH - Hafenstraße 3, 77694 Kehl - Deutschland

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected