



**SIENTO RECYCLE UNI Lin 11**  
Printing support



**6045 Céladon 135**  
Print pattern



Visual not taking into account the printing medium, the final rendering may vary according to the chosen medium.

## Printing support **SIENTO RECYCLE UNI Lin 11**

### Print pattern **6045 Céladon 135**

Heavy canvas fabric, the Siento recyclé is woven with mixed dyed yarns which gives this textured linen effect. The warp and weft are made with recycled polyester yarns. Usable as a printing support. Please note : the background can modify the coloristic rendering.

#### Technical properties



Flame retardant



Thermal



Acoustic



Recycled fabrics

**Applications** Curtains - Cushions - Roman blinds - Panel curtains - Bedspreads - Valences - Seating - Bed runners

**Composition** 80% recycled polyester FR / 20% polyester FR

**Weight** 330 g/m<sup>2</sup>

**Width** 290 cm

**Fabric direction** Room high or standard direction

**Fitting** ↔ 32.0 cm ↓ 32.0 cm

**Maintenance advice**

**Label** France Terre Textile / OEKO-TEX STANDARD 100 Recyclé

**Minimum order** 25 linear(s) meter(s)

## Technical characteristics

|                 |   |
|-----------------|---|
| Flame retardant | M1 / B1 / IMO PASS / UNI 8456 / 9174 Classe Uno   |
| Acoustic        | Noise reduction coefficient (NRC) : <b>0.73</b>   |
| Optical index   | Light reflexion : <b>41 %</b><br>Light absorption : <b>51 %</b><br>Light transmission : <b>8 %</b>  |
| Thermal index   | Solar reflexion : <b>55 %</b><br>Solar absorption : <b>29 %</b><br>Solar transmission : <b>16 %</b><br>UV transmission : <b>5 %</b><br>Gtot : <b>Gt 39 % Fc 66 %</b>  |
| Resilience      | Lightfastness (units Class/8) <b>6</b><br>Pilling <b>4-5</b><br>Dimensional Stability (%)<br>Warp <b>-1,5</b><br>Weft <b>-1,5</b><br>Martindale (Cycles) <b>90000</b><br>Breaking Elongation<br>Warp <b>41</b><br>Weft <b>44</b><br>Breaking load (daN)<br>Warp <b>180</b><br>Weft <b>150</b> |