



**SOLLY BPI 00**  
Printing support



**MURA MASTIC 48**  
Print pattern

## Printing support **SOLLY BPI 00** Print pattern **MURA MASTIC 48**

Textured Printing base fabric. the linen look weft creates a light irregular texture which allows it to be easily printed by transfer sublimation.

### Technical properties



Flame retardant

**Applications** Roman blinds - Panel curtains - Curtains






**Composition** 50% polyester FR recyclé/50% polyester FR

**Weight** 240 g/m<sup>2</sup>

**Width** 280 cm

**Fabric direction** Room High Direction

**Fitting** ↔ 13.0 cm ↓ 13.0 cm

**Maintenance advice**     

**Label** France Terre Textile / OEKO-TEX STANDARD 100 Recyclé

**Minimum order** 25 linear(s) meter(s)



Visual not taking into account the printing medium, the final rendering may vary according to the chosen medium.

## Technical characteristics

Flame retardant

M1 / B1 / UNI 8456 / 9174 Classe Uno

Resilience

|                               |              |
|-------------------------------|--------------|
| Lightfastness (units Class/8) | <b>4</b>     |
| Pilling                       | <b>3</b>     |
| Dimensional Stability (%)     |              |
| Warp                          | <b>-3</b>    |
| Weft                          | <b>-1</b>    |
| Martindale (Cycles)           | <b>25000</b> |
| Breaking Elongation           |              |
| Warp                          | <b>36</b>    |
| Weft                          | <b>36</b>    |
| Breaking load (daN)           |              |
| Warp                          | <b>170</b>   |
| Weft                          | <b>60</b>    |

# Print pattern MURA



MURA NOIR 10



MURA GLACIER 43



MURA GRENAT 56



MURA OLIVE 61



MURA SAPHIR 106



MURA TERRE 107



MURA ROSE 129



MURA MINERAL 157



MURA DUNE 170



MURA ETAIN 180



MURA SAVANE 185