



VEGA 00 BPI 00
Printing support



ELAINA Ivoire 115
Print pattern



Printing support **VEGA 00 BPI 00** Print pattern **ELAINA Ivoire 115**

Blackout print support with velvet look

Technical properties



Flame retardant

Applications Roman blinds - Panel curtains - Curtains

Composition 100% polyester with white flocked acrylic backing

Weight 390 g/m²

Width 260 cm

Fabric direction Room High Direction

Fitting ↔ 0.0 cm ↓ 0.0 cm

Maintenance advice     

Label

Minimum order 25 linear(s) meter(s)



Visual not taking into account the printing medium, the final rendering may vary according to the chosen medium.

Technical characteristics

Flame retardant

EN13773 : 2003 Class 1 / BS 5867 TYPE B / B1 / IMO PASS

Resilience

Lightfastness (units Class/8)

4

Dimensional Stability (%)

Warp

-1

Weft

0

Breaking Elongation

Warp

69

Weft

106

Breaking load (daN)

Warp

52


Weft

41


Print pattern ELAINA



ELAINA Gris 91




ELAINA Violine 105




ELAINA Ocre 03




ELAINA Lin 11



ELAINA Bergamote 121




ELAINA Rose 129




ELAINA Pacifique 54




ELAINA Beige 63



ELAINA Céladon 135




ELAINA Saphir 106




ELAINA Anis 62




ELAINA Rouge 21




ELAINA Hortensia 134



ELAINA Prairie 125




ELAINA Graphite 77




ELAINA Lierre 124




ELAINA Naturel 26



ELAINA Genêt 06



ELAINA Gentiane 16




ELAINA Navy 120

drapilux
By Sotexpro


DRAPILUX GmbH - Hofenstraße 3, 77694 Kehl - Deutschland

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected


Print pattern ELAINA




ELAINA Chamois 111



ELAINA Turquoise 53



ELAINA Anthracite 38



ELAINA Fiesta 131

drapilux
By Sotexpro

DRAPILUX GmbH - Hafenstraße 3, 77694 Kehl - Deutschland

Non-contractual photos and colors - Indicative fitting - Fitting may vary depending on support selected